

Flush and Semi-flush

Skirts for 2-pc Adjustable Canopy



Description

The Flush and Semi-flush skirts have been designed to be used with the cup used with the 2-pc Adjustable Canopy. The flush skirt provides for concealment of the sprinkler drop penetration through standard ceiling materials. The flush skirt allows for a low profile installation of the standard pendent cup. The semi-flush skirt is similar to the flush skirt with a slightly taller profile. Both skirts feature friction fit for a secure installation without the use of any special tools. Both skirts may be used with 1/2" IPS, 3/4" IPS and the 2-pc 1/2" IPS cups. Adjustment range is 0-1.25".

Installation

Proper installation of the sprinkler escutcheon can be accomplished with tools ordinarily found on the job site. The installer must make sure that the reducing coupling on the drop nipple does not exceed 2" outside diameter. Turn the escutcheon cup onto the sprinkler threads then install the sprinkler into the reducing

coupling using the manufacturers sprinkler installation instructions. After the finished ceiling is installed, push the skirt over the cup so that it is flush against the ceiling. Upon system activation, leaks can be detected by observing accumulation of moisture at the "weep" hole.

Specifications

Material:

.020" cold rolled steel

Standard threads:

1/2" or 3/4" IPS

Standard finishes:

Chrome

Brass

White

Off white

Profile: (distance from base material.)

Flush 0.085"

Semi-flush 0.345"

Depth:

Min. 0"

Max. 1.25"

Base coverage:

3.75"