

Concealed Sprinkler Coverage Plate



Description

Concealed Sprinkler Coverage Plates provide increased coverage for the concealed sprinkler cover against the ceiling or wall material where the sprinkler is installed. AHJ's within certain earthquake zones require a minimum of 1" clearance between the sprinkler or sprinkler drop and the material it penetrates. Fits most existing concealed sprinkler cover plates*. See inset for known applications.* May fit other concealed cover plates

Installation

No tools are required for installation of the Concealed Coverage Plate. Simply slide the concealed cover through the ID of the coverage plate then install or re-install the concealed cover on to the retainer. Adjust the concealed cover into place against the finished surface according to each individual manufactures'

instructions. Follow sprinkler manufacturers' instructions for the proper installation of concealed sprinklers. Check with AHJ in installation jurisdiction for acceptance.

Specifications

Material:
.020" cold rolled steel

Standard finishes:
Chrome
White

Coverage:
5" OD (2.25" ID)

Item Numbers:

01-494 5" Coverage Chrome
01-495 5" Coverage White

Fits*:
RASCO G4, RFC43
TYCO RFII
VIKING VK456, VK457,
VK461, VK462, VK463,
VK464, VK465, VK632

*Checked for mechanical clearance only. Check with AHJ for acceptance in the jurisdiction where being installed.