

Open Snoot

MNPT x FNST Connection



Description

The single outlet open snoot is constructed of cast brass*. The single swivel is complete with gasket and comes standard with pin lugs. Outlet is MNPT x FNST. (Plugs, break caps and signs sold separately or in a kit.)

Installation

Installation can be achieved with tools readily available in the field using common installation practices. Make sure male threads of the snoot are liberally coated with a pipe thread sealant such as PipeFit Thread Sealant with PTFE or PTFE Thread Sealant Tape. Tighten the snoot until hand tight. Tighten one additional turn past hand tight to achieve a water tight seal of the threads. **DO NOT OVERTIGHTEN! Over Tightening may cause thread failure as well as cracking of the snoot body.**

*Contains lead. Not for use in water systems intended for human consumption.

Specifications

Material:

Cast brass*

Size:

1 1/2 MNPT x 1 1/2 FNST

1 1/2 MNPT x F Swivel*

2 FNPT x F Swivel*

2 1/2 MNPT x F Swivel*

3 MNPT x 2 1/2 MNST

3 MNPT x 3 FNST

*Available Swivels:

NST 3.0686 x 7.5T

CF 2.9900 x 7.5T

BCT 3.0000 x 8 TP

NYFD 3.0300 x 8 TP

QST 3.0310 x 7 TP

CIN-new 3.0580 x 6 TP

PHX 3.0620 x 6 TP

TEM 3.0750 x 6 TP

CLV 3.0780 x 8 TP

CIN-old 3.0930 x 6 TP

ONT 3.1250 x 5 TP

DET 3.1250 x 7.5T

NovaSco 3.2300 x 5 TP

Dayton 3.2340 x 6 TP

Richmon 3.3120 x 8 TP

Raleigh 3.3400 x 6 TP



Fire Protection Products, Inc

6241 Yarrow Dr., Suite A, Carlsbad, CA 92011-1541

For questions: 1 800 344-1822 • 1 800 344-3775 fax • www.fpfi.com